



CEMENTING MACHINE WITH SINGLE ROLLER Model XRGJ
 CEMENTING MACHINE WITH DOUBLE ROLLER Model XRGJ



This Machine is used for coating glue onto plane material with different thickness in shoes-making, packing industry, wooden-processing, toy, leather, zipper-making, Clothing and electronic, etc, it can substitute double tape(to avoid unnecessary separating-paper)and has features as cost saving and environment friendly.

This machine applies pneumatic glue-sending method. The thickness, shape or bend of work piece as well as edge-cut, speed and glue volume can be adjusted, The telfom-processed, glue tank can prevent it from carbonation of thermosol, thermosol and also has feature of nonstick.

Remark: To satisfy different requirements of customers, our factory has specially designed a model characterized by one-time roll gluing of hot-melt adhesive for zipper, as shown in figure .First transfer out the two flexible spacers 24.The two spring leaves 26 will respectively press the flexible spacers 24 under the effect of elastic force which can guarantee that the zipper can pass smoothly during the roll gluing operation. the operation methods are same as those above mentioned.

Electric power(kw)	Working Temperature(°C)	Range of air pressure(Mpa)	Outline size(mm)	Weight(kg)
--------------------	-------------------------	----------------------------	------------------	------------

1	150-180	≤ 0.4	420×360×630	30
Remark: The width of roller:4-22mm,other size can be made according to customer's need.				